

### Product Information Sheet

#### Product

## Polymex® PP22C

#### Product Description


Polymex® PP22C is a bi-axially oriented, co-extruded clear polyester film which is one side corona treated, one side chemically treated to promote adhesion of A1-metallizing, printing inks, adhesives and coatings (self-test recommended). In addition the food contact approval allows it to be used in food contact applications. Polymex® PP22C is not suitable for laminating processes.

Available in thicknesses 12 – 75 micron.

#### Key Features

- Excellent Clarity
- Ideal for A1-metallizing
- Good adhesion to printing inks, adhesives and coatings

#### Structure of Polymex® PP22C



Adhesion promoting surface  
Clear PET  
Adhesion promoting surface

Property	Test Method	Unit	Value	
Film Thickness	-	micron	12	23
Film Yield	-	M <sup>2</sup> /Kg	59	31
Unit Weight	-	g/m <sup>2</sup>	17	32
Haze	ASTM D 1003-61	%	1.8	2.2
Tensile strength at break MD TD	ISO 527-1-2	N/mm <sup>2</sup>	230 260	230 260
Elongation at break MD TD	ISO 527-1-2	%	110 99	115 94
Density	ASTM D 1505-68	g/cm <sup>3</sup>	1.395 (23°C)	
Coefficient of friction (static)	ASTM D 1894	-	0.4	
Shrinkage MD TD	150°C, 15 min	%	1.4 0.2	1.3 0.1

'MD' - Machine direction. 'TD' - Transverse direction

#### Applications

Polymex® PW122 complies with EU food contact legislation 2002/72/EC, and amendments with FDA regulation 21 CFR 177.1630

*The information above is given in good faith and should be considered as a guide not a specification.*



BS EN 14644 : 1999  
CLEANROOM CLASS 8

+44 (0) 20 7740 9740  
[www.packagingfilm.co.uk](http://www.packagingfilm.co.uk)