

Product Information Sheet

Product

Polymex® PP261

Product Description


Polymex® PP261 is an industrial clear film which is chemically treated on one side externally to promote adhesion to inks and coatings. Polymex® PP261 is ideal for use in applications where high transparency is required, such as label lamination and reprographics. The treated surfaces offer fantastic adhesion to typical inks, adhesives and is suitable high barrier laminates on food packaging (self-test recommended).

Available in a thickness of 12 micron.

Key Features

- Excellent clarity and thermal stability
- Ideal for printing, laminating and food packaging
- Good adhesion to inks, coatings and adhesives

Structure of Polymex® PP261



PVDC surface
Clear PET
Untreated surface

Property	Test Method	Unit	Value
Film Thickness	-	micron	12
Film Yield	-	M ² /Kg	59
Unit Weight	-	g/m ²	17
Haze	ASTM D 1894-78	%	4.5
Tensile strength at break MD TD	ASTM D 822	daN/mm ²	18 20
Elongation at break MD TD	ASTM D 822	%	120 100
Co-efficient of friction (static)	ASTM D 1894	-	0.50
Roughness Ra Value MD TD	DIN 4768	nm	10
Shrinkage MD TD	30 min at 150°C	%	1.8 0.1

'MD' - Machine direction. 'TD' - Transverse direction

Applications

Polymex® PP261 complies with EU food contact legislation 2002/72/EC, and amendments with FDA regulation 21 CFR 177.1630

The information above is given in good faith and should be considered as a guide not a specification.



BS EN 14644 : 1999
CLEANROOM CLASS 8

+44 (0) 20 7740 9740
www.packagingfilm.co.uk