

Product Information Sheet

Product

Polymex® PZMSE

Product Description


Polymex® PZMSE is an external side metallised, internal side acrylic coated polyester film to promote adhesion to ink and solvent coatings (self-test recommended). In addition, Polymex® PZMSE is food approved so it can be utilised in food contact applications.

Available in thicknesses of 8 and 12 micron.

Key Features

- High gloss, dimensionally stable metallized coating protects against natural and UV light
- Ideal for food packaging which requires high quality printing
- Good for decorative applications such as laminated luxury boxes and frozen food

Structure of Polymex® PZMSE



Metallised surface
Low haze PET
Adhesion promoting surface

Property	Test Method	Unit	Value
Film Thickness	-	micron	12
Film Yield	-	M ² /Kg	59
Unit Weight	-	g/m ²	17
Optical density	Macbeth	-	2.2
Tensile strength at break MD TD	ASTM D 822	daN/mm ²	20 22
Elongation at break MD TD	ASTM D 822	%	130 100
Light transmission	Macbeth	%	0.6
Metal adhesion Heat seal test	Internal method	N/38mm	1.5
Shrinkage MD TD	at 150°C	%	1.5 0.5

'MD' - Machine direction. 'TD' - Transverse direction

Applications

Polymex® PZMSE is a versatile packaging film which is suitable for print and complies with EU food contact legislation 2002/72/EC, and amendments with FDA

The information above is given in good faith and should be considered as a guide not a specification.



BS EN 14644 : 1999
CLEANROOM CLASS 8

+44 (0) 20 7740 9740
www.packagingfilm.co.uk